

NON-WOVEN DESIGN2WALL UV 150

matt 2500, 150 g/m²

Economical non-woven wallpaper with a natural surface

The Non-woven design2wall UV 150 matt is an uncoated non-woven wallpaper for inkjet printing with latex and UV inks. This product is suitable for digital printing of wall decorations and wallpapers. It has a matt finished, natural surface and can be pasted without further surface protection, with standard non-woven wallpaper paste. It is flame retardant and certified.

Advantages

- High wet and dry strength
- Dry strippable
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1
- Hang using standard non-woven wallpaper paste



General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

Physical data

Name	Value	Norm
Weight [g/m ²]	150	ISO 536
Thickness (paper) [µm]	320	ISO 534
ISO Brightness [%]	88	ISO 2470-1
Opacity [%]	90	ISO 2471
Tensile strength MD [N/15mm]	148	ISO 1924-3/2/300
Tensile strength CD [N/15mm]	94	ISO 1924-3/2/300
Wet tensile strength MD [N/15mm]	47	ISO 3781
Wet elongation CD (Fenchel) [%]	0.1	A 10-011/27
Water absorbency (Cobb) [g/m ²]	18	ISO 535

Technologies



Properties

