



# DURASOL HEAVY 450

satin 3508, 430 µm

Dimensionally stable, hard-PVC film with a look and feel similar to cardboard for installation in pop-up systems

DuraSOL Heavy is ideal for the production of graphics for exhibition wall and display systems printed with solvent and UV inks. Its robust, hard-PVC base guarantees outstanding stiffness and is tear resistant and waterproof. This makes the material suitable for use in short- to medium-term outdoor applications. Prints impress with a combination of high colour brilliance and good image sharpness that creates an outstanding printed image.

## Advantages

- Brilliant colour reproduction
- Waterproof prints for short- to medium-term outdoor applications
- High scratch resistance
- High stiffness

## General tips

The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10 to 30 C. Keep the product in the original packaging (cardboard box and PE bag). It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

The coating allows a very short drying time even with low heating temperatures on eco- or true-solvent printers. The heaters should be set at maximum 30°C to avoid waves.

## Physical data

Name	Value	Norm
Thickness (film) [µm]	430	ISO 4593
Weight [g/m <sup>2</sup> ]	630	ISO 536

## Technologies



## Properties



The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.