



EXHIBITION STAND  
CONSTRUCTION / POS /  
EVENTS

# SYNTISOL PP FILM 170

satin 3629, 170 µm

Universal satin polypropylene film for indoor and outdoor displays and A-boards

In combination with solvent, latex and UV inks, this tear resistant PP film is suitable for the production of A-boards, information stands and other POS applications. In combination with its special coating, the robust base material of this film makes it suitable for short- to medium-term use in outdoor applications. The satin, paper like surface hinders interfering reflections and delivers brilliant prints. With a thickness of 170 µm, the material provides easy handling and optimum processing characteristics. For example, the film can be easily mounted with and removed from double-sided adhesive tape without any problems.

## Advantages

- Brilliant colour reproduction
- Splashproof prints for short- to medium-term outdoor applications
- Tear resistant
- Quick further processing
- High scratch resistance
- PVC free

## General tips

To sustain quality of this media, it should be stored and converted under the following conditions: 35 – 65 % humidity with temperatures of 10 – 30°C. Keep the product in original packaging (cardboard box and PE bag). Cotton gloves should always be worn when handling inkjet media to avoid fingerprints.

## Physical data

Name	Value	Norm
Thickness (film) [µm]	170	ISO 4593
Weight [g/m <sup>2</sup> ]	130	ISO 536

## Technologies



## Properties

