



# VINYL FILM OUTDOOR SA 280

matt 0729, 145 µm

Economic, universal and permanent self-adhesive vinyl film (PVC) with a high white, water-resistant and matt inkjet coating. The main application is for indoor use, temporary also for outdoor application.

## Advantages

- Flexible PVC base (vinyl)
- Matt, water-resistant coating
- Permanent, waterbased glue
- Unprotected, suitable for short-term outdoor applications (max.2 months)

## General tips

Storage:

Application to objects:

The surface must be smooth, dry and clean of any dirt or grease. For optimal adhesive bonding a processing temperature between 15 and 25°C should be maintained. The adhesive film should not be used on objects made of PVC, polystyrol, polycarbonate or polyamide, nor objects painted with acrylic paint. Avoid sticking to objects that have been freshly painted.

To remove the film after use – glue residues can be removed using soapy water or petroleum (attention – the resistance of the surface should be checked before using any detergent).

To maintain the quality storage and processing should be done in a climate of 35 to 65% relative humidity at temperatures from 10 to 25°C. The product should be kept in its original packaging and optimally used within 4 months of delivery.

## Physical data

Name	Value	Norm
Weight [g/m <sup>2</sup> ]	290	ISO 536
Weight (without liner/ adhesive) [g/m <sup>2</sup> ]	140	ISO 536
Thickness (film) [µm]	280	ISO 4593
Thickness (film without liner / adhesive) [µm]	145	4593
Adhesion strength on glass (24h) [N/25mm]	14	FTM 1
pH value	5-6	DIN 53124

## Technologies



## Properties



- Cold lamination
- Water-resistant / Waterfast